
Data Sheet Lithium Manganese Dioxide CR 1620



Type Number.....	6620
Designation IEC.....	CR 1620
System.....	Li-Manganese dioxide/ Organic Electrolyte
UL Recognition.....	MH 13654 (N)
Nominal Voltage.....	3 V
Typical Capacity C.....	70 mAh

Temperature Ranges	min	max.
Storage.....	-55°C	70°C
Discharge.....	-20°C	65°C

Dimensions	min	max.
Diameter (A)	15,7	16,0
Height (B).....	1,8	2,0
Shoulder Diameter [E]	12,9	
Shoulder Height [C]	0,2	

Weight (approx.)..... 1,33 g

Typical Capacities (at 20°C)

Discharge Type	**Load**	**End Voltage:**	**2.0V**
Continuous 24h/d, 7d/w	47000 Ω	Time::	1416 h

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries.

All Data contained herein is for single cells
For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Consumer Batteries GmbH & Co. KGaA
Alfred-Krupp-Str. 9, 73479 Ellwangen/Germany

Subject to change without prior notice!
Date of issue: 2022-02-02

Phone: (+49) 7961/83-0, Fax: (+49) 800-827-8274